

SANY[®]
QUALITY CHANGES THE WORLD



MATERIAL HANDLING MACHINE

SANY MARINE

As a key division of SANY International, SANY Marine operates from Zhuhai, Guangdong Province, specializes in MPM (RS, ECH), port crane (RTG, RMG, STS, Jib Crane, MHC and SC), and logistics equipment (material handlers, heavy-duty forklifts, ETT, and TH)

CONTENTS

SMHW30	▶ 10
SMHW30G5	▶ 12
SMHC35	▶ 14
SMHW40	▶ 16
SMHW40G5	▶ 18
SMHW40-E	▶ 20
SMHC45V	▶ 22
SMHW48V	▶ 24
SMHW48G5	▶ 26
SMHW48V-D	▶ 28
SMHC50V-D	▶ 30
SMHC70	▶ 32
SMHW80	▶ 34
SMHC100	▶ 36
SMHC160	▶ 38
SMHR200	▶ 40
Cabin	▶ 42
Attachments	▶ 44
Construction Cases	▶ 46

► SANY Marine launched its first material handler in 2018, with total sales over 1000 units.

The product line includes 30 to 200 tons, with both wheeled and crawler chassis options.



MATERIAL HANDLING MACHINE

► Wheel Type

SMHW30

- Optional Boom
K12, K14
- Overall Weight
33.5-36t
- Engine power
180kW/145kW



SMHW40E/SMHW40

- Optional Boom
K14, K15, K17
- Overall Weight
39.5t
- Main pump power
160kW
- Swing system power
80kW
- Engine power
168kW/175kW



► Rail Gantry

SMHW48

- Optional Boom
K14, K18, K20
- Overall Weight
45t-47t
- Engine power
212kW/252kW



SMHW80

- Optional Boom
K18, K22, K24
- Overall Weight
97t-105t
- Engine power
260kW



SMHR200

- Optional Boom
K31, K35
- Overall Weight
220t-235t
- Engine power
2*353kW



► Crawler-Type

SMHC35

- Optional Boom
K12
- Overall Weight
32.5t
- Engine power
147kW



SMHC45V

- Optional Boom
K11, K14
- Overall Weight
42t-44t
- Engine power
212kW



SMHC50V-D (Towing Power)

- Optional Boom
K11, K14
- Overall Weight
43t-44t
- Engine power
160kW



SMHC70

- Optional Boom
K18, K20, K22
- Overall Weight
66t-71t
- Engine power
260kW



SMHC100

- Optional Boom
K18, K22, K24
- Overall Weight
97t-105t
- Engine power
260kW



SMHC160

- Optional Boom
K22, K26
- Overall Weight
170t-175t
- Engine power
2*235kW



► Material Handler Overview

- A material handler is a high-efficiency multi-purpose equipment for bulk/general cargo loading, unloading, and stacking. It executes specialized operations including grabbing, clamping, hoisting, and cutting in specific applications.
- It is widely used in scrap metal, mining, timber, waste management, as well as ports, rail terminals, logistics yards, and industrial warehouses. Combining functions of cranes, loaders, and excavators, it can perform partial roles of these machinery.



Port Operations



Scrap Metal Handling




Coal Handling



Bulk Cargo Handling

► Diesel vs Electric Comparison

- The boom drive utilizes an independent positive/negative swing angle two-quadrant piston pump system that harnesses potential energy during boom lowering.
- The slewing mechanism employs permanent magnet synchronous motor drive with regenerative braking capability for kinetic energy recovery.
- Delivers industry-leading energy efficiency with an average runtime of up to 8 hours.
- Operating costs are as low as 24% compared to conventional diesel-powered models.



► Electro-Hydraulic Maindrive



► Slewing drive



► CATL Battery Pack

► Construction


SMHW30




Product Parameters

Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHW30	CONFIGURATION		UNIT	SMHW30		
Power System	Engine	Model	-	Mitsubishi D06FRC	Hydraulic System	Max. System Pressure	MPa	34.5		
		Rated Power	kW/rpm	147/2100		Hydraulic Oil Tank	L	230		
		Torque	Nm/rpm	750/1350	Slewing Gear	Max. Rotating Speed	rpm	8		
		Emission	-	com III		Cabin	Cabin Lift Height	mm	2650	
		Oil Tank Capacity	L	465	Basic Parameters	Boom Configuration	m	12	14	
Chassis	Track Width		mm	2387			m	Boom 7.3	Boom 8.6	
	Wheel Base		mm	2800			m	Stick 5.1	Stick 5.6	
	Support Width(lengthways)		mm	4750			Max. Operating Radius	m	10.5	13.5
	Support Width(crosswise)		mm	4140		Max. Operating Height	m	12	13.5	
	Turning Radius		mm	8000		Max. Operating Depth	m	-3	-3	
Hydraulic System	Max. Travelling Speed		km/h	20		Max. Operating Radius (Grab Not Included)	t	4.6	3.4	
	Type Of Control	-	Electronically Controlled Positive Flow System	Main Pump		Rated Flow	L/min	2×260		


Dimensions



SMHW30 Lift capacities of material handler
(Boom 7.3m, Stick 5.1m, Unit:t)



SMHW30 Lift capacities of material handler
(Boom 8.6m, Stick 5.6m, Unit:t)



- Load-sensing hydraulics, 10% lower fuel use
- Optimized engine-pump match
- Auto-idle & multi-speed throttle
- 300ms response, 400t/h efficiency


SMHW30G5



► Product Parameters


Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHW30G5	CONFIGURATION		UNIT	SMHW30G5		
Power System	Engine	Model	-	CumminsB6.7	Slewing Gear	Max. Rotating Speed	rpm	8		
		Rated Power	kw/rpm	145/2000						
		Torque	Nm/rpm	847/1500	Cabin	Cabin Lift Height	mm	2650		
		Emission	-	EU stage V						
		Fuel Tank	L	465						
Chassis System	Track Width		mm	2387	Basic Parameters	Boom Configuration	m	12	14	
	Wheel Base		mm	2800			m	Boom 7.3 Boom 8		
	Support Width(lengthways)		mm	4720			m	Stick 5.1 Stick 6		
	Support Width(crosswise)		mm	3973			Max. Operating Radius	m	12	13.5
	Turning Radius		mm	8000				m	12	13.5
	Max. Gradeability		%	35		Max. Operating Depth		m	-3	-3
	Max. Travelling Speed		km/h	20			Max. Operating Radius Load (Grab Not Included)	t	4.5	3.2
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System	Max. Operating Radius Load (Grab Not Included)	t		4.5	3.2	
	Main Pump	Rated Flow	L/min	2×260						
	Max. System Pressure		MPa	32						
	Hydraulic Oil Tank		L	230						

► Dimensions




► Scope Of Work

SMHW30G5 Lift capacities of material handler
(Boom 7.3m, Stick 5.1m, Unit:t)



SMHW30G5 Lift capacities of material handler
(Boom 8m, Stick 6m, Unit:t)



- Cummins engine, strong power
- Reinforced undercarriage, stable and safe
- Fits scrap, wood, recycling scenarios


SMHC35



► Product Parameters


Technical Parameter					Configuration Parameter			
ITEM			UNIT	SMHC35	CONFIGURATION		UNIT	SMHC35
Power System	Engine	Model	-	Mitsubishi D06FRC	Hydraulic System	Max. System Pressure	MPa	34.5
		Rated power	kW/rpm	147/2100		Hydraulic Oil Tank	L	230
		Torque	Nm/rpm	750/1350	Slewing Gear	Max. Rotating Speed	rpm	8
		Emission	-	com III		Cabin Lift Height	mm	2650
		Oil Tank Capacity	L	465	Basic Parameters		m	12
Traveling Gear	Track width		mm	2590		Boom Configuration	m	Boom 6.8
	Wheel Base		mm	3830			m	Stick 5.6
	Track Width		mm	600		Max. Operating Radius	m	10.5
	Max. Travelling Speed		km/h	5		Max. Operating Height	m	10.5
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System		Max. Operating Depth	m	-6
	Main Pump	Rated Flow	L/min	2×260		Max. Operating Radius (Grab Not Included)	t	3.4

► Dimensions



► Scope Of Work

SMHC35 Lift capacities of material handler
(Boom 6.8m, Stick 5.6m, Unit:t)



- Load-sensing system, 10% fuel savings
- Efficient engine-pump coordination
- Auto-idle & throttle control
- 300ms response, 200t/h throughput

SMHW40




- 20% less fuel than 48t model
- Modular boom, longer fatigue life
- Auto-dust cooling with reversible fan
- Heated suspension seat, 50% less vibration

► Product Parameters


Technical Parameter				Configuration Parameter			
ITEM			UNIT	SMHW40			
Power System	Engine	Model	-	Deutz D09S3			
		Rated Power	kw/rpm	175/2000			
		Torque	Nm/rpm	1200/1100~1400			
		Emission	-	Stage III			
		Fuel Tank	L	600			
Chassis System	Trackwidth		mm	2386			
	Wheel Base		mm	3000			
	Support Width(lengthways)		mm	5020			
	Support Width(crosswise)		mm	4400			
	Turning Radius		mm	8500			
	Max.Gradeability		%	30			
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System			
	Main Pump	Model	-	kawasaki			
		Rated Flow	L/min	2×288			
	Max.System Pressure		MPa	32			
	Hydraulic Oil Tank		L	320			
CONFIGURATION			UNIT	SMHW40			
Hydraulic System	Max. System Pressure		MPa	34.5			
Cabin	Cabin Lift Height		mm	2650			
Basic Parameters	Boom Configuration		m	17	15		
			m	Boom 9.8	Boom 8.8		
			m	Stick 7.5	Stick 6		
	Max. Operating Radius	m	16.5	15			
	Max. Operating Height	m	10.5	16.5			
	Max. Operating Depth	m	-5	-4.5			
	Max. Operating Radius Load (Grab Not Included)	t	3.9	5.1			

► Dimensions



► Scope Of Work

SMHW40R Lift capacities of material handler
(Boom 9.8m, Stick 7.5m, Unit:t)




SMHW40G5



Product Parameters


Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHW40G5	CONFIGURATION		UNIT	SMHW40G		
Power System	Engine	Model		CumminsB6.7	Hydraulic System	Slewing Bearing	-	Sany		
		Rated power	kw/rpm	168/2000		Max.Rotating Speed	rpm	8		
		Torque	Nm/rpm	1044/1500						
		Emission	min	EU stage V						
		Fuel Tank	L	600						
Chassis System	Trackwidth		mm	2386	Cabin	Cabin Lift Height	mm	2650		
	Wheel base		mm	3000		Boom Configuration	m	17	15	
	Support width(lengthways)		mm	5020	m			Boom 9.8	Boom 8	
	Support width(crosswise)		mm	4400				m	Stick 7.5	Stick 6
	Turning radius		mm	8500					m	16.5
	Max.Gradeability		%	30	Max. Operating Height			m		18
	Max.Travelling Speed		km/h	20		Max. Operating Depth	m		-5	-4.5
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System	Basic Parameters			Max. Operating Radius	m	3.9
	Main Pump	Model	-	Kawasaki		Max. Operating Radius load (Grab Not Included)	t	3.9	5.1	
		Rated Flow	L/min	2×288						
	Main Valve		-	Kawasaki						
	Reducer		-	Sany						
	Boom Cylinder		-	Sany						
	StickCylinder		-	Sany						
	Max.System Pressure		MPa	32						
	Hydraulic Oil Tank		L	320						

Dimensions



Scope Of Work

SMHW40G Lift capacities of material handler
(Boom 9.8m, Stick 7.5m, Unit:t)



- 20% less fuel than 48t model
- Modular boom, longer fatigue life
- Auto-dust cooling with reversible fan
- Heated suspension seat, 50% less vibration


SMHW40E



Product Parameters


Configuration Parameter					Configuration Parameter						
ITEM			UNIT	SMHW40E	CONFIGURATION		UNIT	SMHW40E			
Power System	Electric Motor	Model	-	Weiteli	Slewing Gear	Max. Rotating Speed	rpm	8			
		Rated Power	kW/rpm	160/2040, 80/1900							
		Battery Voltage	VDC	437	Cabin	Cabin Lift Height	mm	2650			
		Electronic Control	-	Weiteli							
	Battery	Model	-	CATL	Lubrication System	Mode	-	Automatic Lubrication			
Battery Charge Level		kWh	507								
Chassis	Track Width		mm	2385	Basic Parameters	Boom Configuration	m	17	15	14	
	Wheel Base		mm	3000				m	Boom 9.8	Boom 8.8	Boom 8.8
	Support Width (lengthways)		mm	5020			m		Stick 7.5	Stick 6.6	Stick 5.6
	Support Width (crosswise)		mm	4400				Max. Operating Radius (Excluding Spreader)	m	16.5	14.5
	Turning Radius		mm	8500		Max. Operating Height (Excluding Spreader)	m		18	15	15
	Maximum Gradeability		%	30			Max. Operating Depth (Excluding Spreader)		m	-4.5	-4.5
	Max. Travelling Speed		km/h	20		Max. Operating Radius (Grab Not Included)		t	4	4.5	5
Hydraulic System	Type Of Control		-	Electrically Controlled Positive Flow System			Max. Operating Depth (Excluding Spreader)	m	-4.5		
	Main Pump Reducer	Rated Flow	L/min	2×380							
		Model	-	Stub Tooth							
	Maximum System Pressure		MPa	34		Max. Operating Radius (Grab Not Included)	t	4			
	Hydraulic Oil Tank		L	350							

Dimensions




Scope Of Work

SMHW40-E Lift capacities of material handler
(Dynamic Ar 9.8m Bucket Rod 7.5m unit:t)



SMHW40-E Lift capacities of material handler
(Dynamic Ar 8.8m Bucket Rod 6.6m unit:t)



- Energy recovery, 80% lower cost vs diesel
- 7-9h runtime with high-capacity battery
- Electric control + independent swing, +20% efficiency
- Compact wheeled chassis, strong climbing, agile movement


SMHC45V



► Product Parameters


Configuration Parameter					Configuration Parameter				
ITEM			UNIT	SMHC45V	CONFIGURATION		UNIT	SMHC45V	
Power System	Engine	Model	-	Isuzu 6HK1	Slewing Gear	Max. Rotating Speed	rpm	8	
		Rated power	kW/rpm	212/2000	Cabin	Cabin Lift Height	mm	2650	
		Torque	Nm/rpm	1080/1500		Boom Configuration	m	11	14
		Emission	-	com III			m	Boom 7	Boom 8.6
		Oil Tank Capacity	L	600	m	Stick 4.5	Stick 6		
Undercarriage	Track Gauge		mm	2590	Basic Parameters	Boom Mounted At The Pivot Point Of The Slewing Platform	-	Upper Pivot Point	Upper Pivot Point
	Wheelbase		mm	4140		Max. Operating Radius	m	10.5	13.5
	Track Width		cm	600		Max. Operating Height	m	12	15
	Max. Travelling Speed		km/h	5		Max. Operating Depth	m	-1.5	-3
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System		Max. Operating Radius (Grab Not Included)	t	5.9	4.1
	Main Pump	Rated Flow	L/min	2×320					
	Maximum System pressure		MPa	32					
	Hydraulic Oil Tank		L	310					

► Dimensions




► Scope Of Work

SMHC45V Lift capacities of material handler
(Boom 7m, Stick 4.5m, Unit:t)



SMHC45V Lift capacities of material handler
(Boom 8.6m, Stick 6m, Unit:t)



- Load-sensing hydraulics, 10% fuel cut
- Optimized powertrain
- Auto-idle & throttle steps reduce loss
- 300ms response, 450t/h handling rate


SMHW48V




► Product Parameters

Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHW48V	CONFIGURATION		UNIT	SMHW48V		
Power System	Engine	Model	-	Isuzu 6HK1	Hydraulic System	Max. System Pressure	MPa	32		
		Rated power	kW/rpm	212/2000		Hydraulic Oil Tank	L	310		
		Torque	Nm/rpm	1080/1500	Slewing Gear	Max. Rotating Speed	rpm	8		
		Emission	-	com III		Cabin	Cabin Lift Height	mm	2650	
		Fuel Tank	L	600			Basic Parameters	Boom Configuration	m	14
Chassis	Track Width		mm	2746	m	Boom 8.6 Boom 10.5				
	Wheel Base		mm	3200	m	Stick 6 Stick 7.5				
	Support width(lengthways)		mm	5400	Max. Operating Radius	m		13.5	16.5	
	Support width(crosswise)		mm	4800		m		15	16.5	
	Turning Radius		mm	8800		m		-4.5	-4.5	
Hydraulic System	Max. Travelling Speed		km/h	20	Max. Operating Height	m				
	Type Of Control		-	Electronically Controlled Positive Flow System	Max. Operating Depth	m				
	Main Pump	Rated Flow	L/min	2×260	Max. Operating Radius (Grab Not Included)	t		6.1	5.1	

► Dimensions



► Scope Of Work



▪ 520t/h productivity

▪ 300ms actuation

▪ 20km/h wheeled chassis, fast relocation

SMHW48G5




Product Parameters

Technical Parameter					Configuration Parameter						
ITEM			UNIT	SMHW48G5	CONFIGURATION		UNIT	SMHW48G5			
Power System	Engine	Model	-	Cummins QSL9	Slewing Gear	Max. Rotating Speed	rpm	8			
		Rated Power	kw/rpm	252/1800							
		Torque	Nm/rpm	1526/1400	Cabin	Cabin Lift Height	mm	2650			
		Emission	min	EU Stage V							
		Fuel Tank	L	600							
Chassis	Track Width		mm	2746	Basic Parameters	Boom Configuration	m	18	20		
	Wheel Base		mm	3200			m	Boom 10.5	Boom 10.5		
	Support Width(lengthways)		mm	5400			m	Stick 7.5	Stick 9.5		
	Support Width(crosswise)		mm	4800							
	Turning Radius		mm	8800							
	Max. Travelling Speed		km/h	20							
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System		Max. Operating Radius	m	17.5	19.5		
	Main Pump		Rated Flow	L/min			2×320	Max. Operating Height	m	18	19.5
	Max. System Pressure		MPa	32			Max. Operating Depth		m	-7	-9
	Hydraulic Oil Tank		L	340					Max. Operating Radius Load (Grab Not Included)	t	4.3


- For ports, timber, dismantling, recycling
- Heavy-duty design for high loads
- Energy-efficient, cost-effective
- Multiple compatible attachments

Dimensions




Scope Of Work

SMHW48G5 Lift capacities of material handler (Boom10.5m, Stick 7.5m, Unit:t)



SMHW48G5 Lift capacities of material handler (Boom10.5m, Stick 9.5m, Unit:t)



SMHW48-D



Product Parameters



Technical Parameter					Configuration Parameter							
ITEM			UNIT	SMHW48-D	CONFIGURATION		UNIT	SMHW48-D				
Power System	Motor	Model	-	XEMC YE2-315L1-4	Slewing Gear	Slewing Bearing	-	SANY				
		Rated power	kw/rpm	160/1485		Max. Rotating Speed	rpm	8				
		Torque	Nm/rpm	1526/1400								
		Voltage	AC	380V,50HZ								
Chassis System	Trackwidth		mm	2746	Cabin	Cabin Lift Height	mm	2650				
	Wheel base		mm	3200		Basic Parameters	Boom Configuration	m	18	20		
	Support width(lengthways)		mm	5400	m			Boom 10.5	Boom 10.5			
	Support width(crosswise)		mm	4680	m			Stick 7.5	Stick 9.5			
	Turning radius		mm	8800	Max. Operating Radius			m	16.5	16.5		
	Max.Gradeability		%	35							Max. Operating Height	m
	Max.Travelling Speed		km/h	5		Max. Operating Depth	m					
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System	Max. Operating Radius (Grab Not Included)			t	4.3	3.5		
	Main Pump	Model	-	Kawasaki								
		Rated Flow	L/min	2×320								
	Main Valve		-	Kawasaki								
	Reducer		-	Sany								
	Boom Cylinder		-	Sany								
	StickCylinder		-	Sany								
	Max.System Pressure		MPa	32								
	Hydraulic Oil Tank		L	380								

Dimensions


Scope Of Work

- Fuel-Saving Hydraulics: 20% lower consumption vs 48t models
- Modular Boom: 30%+ fatigue life extension
- Transport-Ready: 3m×3.5m regulation-compliant dimensions
- Self-Cleaning Radiator: Motor-driven reversible fan
- Enhanced Comfort: Heated air-ride seat + 50% less vibration

SMHW48-D Lift capacities of material handler (Boom 10.5m, Stick 7.5m, Unit:t)



SMHW48-D Lift capacities of material handler (Boom 10.5m, Stick 9.5m, Unit:t)




SMHC50V-D



► Product Parameters

Technical Parameter					Configuration Parameter				
ITEM			UNIT	SMHC50V-D	CONFIGURATION		UNIT	SMHC50V-D	
Power System	E-Motor	Model	-	XEMC YE2-315L1-4	Slewing Gear	Max. Rotating Speed	rpm	8	
		Rated Capacity	kW/rpm	160/1485					
		Input Voltage	V/Hz	380/50	Cabin	Cabin Lift Height	mm	2650	
		Type Of Start	-	Soft Start					
Traveling Gear	Working Gauge		mm	2590	Basic Parameters	Boom Configuration	m	11	14
	Wheel Base		mm	4140			m	Boom 7	Boom 8.6
	Track Width		mm	600			m	Stick 4.5	Stick 6
	Max. Travelling Speed		km/h	5			m		
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System		Max. Operating Radius	m	10.5	13.5
	Main Pump	Rated Flow	L/min	2×297		Max. Operating Height	m	10.5	13.5
	Max. System pressure		MPa	32		Max. Operating Depth	m	-1.5	-3
	Hydraulic Oil Tank		L	310		Max. Operating Radius (Grab Not Included)	t	5.9	4.1


► Dimensions



► Scope Of Work

SMHC50V-D Lift capacities of material handler (Boom 7m, Stick 4.5m, Unit:t)

SMHC50V-D Lift capacities of material handler (Boom 8.6m, Stick 6m, Unit:t)



- Electric drive cuts costs by 65%
- 300ms fast response
- Crawler chassis for tough terrain


SMHC70

Product Parameters


Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHC70	CONFIGURATION		UNIT	SMHC70		
Power System	Engine	Model	-	Deutz D09S3T9	Traveling Gear	Working Gauge	mm	4000		
		Rated Power	kw/rpm	260/2000		Wheel Base	mm	4690		
		Torque	Nm/rpm	1530/1200-1400		Track Width	mm	762		
		Emission	-	EU Stage III		Max. Travelling Speed	km/h	3		
		Oil Tank Capacity	L	600		Max. Rotating Speed	rpm	8		
	E-Motor	Model	-	XEMC YE3-355M-4	Cabin	Cabin Lift Height	mm	2650		
		Rated Capacity	kW/rpm	250/1485		Boom Configuration	m	18	20	22
		Input Voltage	V/Hz	380/ 50			m	Boom 10.5	Boom 12.5	Boom 12.5
		Type Of Start	-	Soft Start			m	Stick 7.5	Stick 7.5	Stick 10
	Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System	Basic Parameters	Max. Operating Radius	m	18	19.5
Main Pump		Rated Flow	L/min	While Using Engine: 2×400 While Using E-Motor: 2×416	Max. Operating Height		m	16.5	18	19.5
					Max. Operating Depth		m	-6	-6	-9
Max. System Pressure		MPa	34.3	Max. Operating Radius (Grab Not Included)	t		7.4	6.6	5.8	
Hydraulic Oil Tank		L	500							

Dimensions


Scope Of Work




SMHC70 Lift capacities of material handler (Boom 10.5m, Stick 7.5m, Unit:t)



SMHC70 Lift capacities of material handler (Boom 12.5m, Stick 7.5m, Unit:t)



SMHC70 Lift capacities of material handler (Boom 12.5m, Stick 10m, Unit:t)



- 6.5t grab, 24s cycle, 2× 16t crane output
- Telescopic crawlers, ground-friendly mobility
- Lightweight, rail-free setup
- Dual power, 65%+ cost saving


SMHW80



Product Parameters

Technical Parameter					Configuration Parameter						
ITEM			UNIT	SMHW80	CONFIGURATION		UNIT	SMHW80			
Power System	Engine	Model		-	Deutz D09S3T9	Slewing Gear	Max. Rotating Speed	rpm	8		
		Rated power		kw/rpm	260/2000						
		Torque		Nm/rpm	1530/1200-1400	Cabin	Cabin Lift Height	mm	2650		
		Emission		-	EU Stage III						
		Oil Tank Capacity		L	600						
	E-Motor	Model		-	-	Basic Parameters	Boom Configuration	m	18	22	24
		Rated Capacity		kW/rpm	-				m	Boom 10.5	Boom 12.5
		Input Voltage		V,Hz	-			m		Stick 7.5	Stick 10
Type Of Start		-	-	Max. Operating Radius	m				18	22	24
Track Width		mm	3120					Max. Operating Height			
Wheel Base		mm	3600	Max. Operating Depth	m				-4.5	-7.5	-9
Support Width(lengthways)		mm	6300				Max. Operating Radius (Grab Not Included)	t			
Support Width(crosswise)		mm	5600								
Turning Radius		mm	9800								
Max. Gradeability		%	20								
Max. Travelling Speed		km/h	10								
Chassis System	Type Of Control		-	Electronically Controlled Positive Flow System							
	Main Pump	Rated Flow	L/min	2×400							
	Max. System Pressure		MPa	34							
	Hydraulic Oil Tank		L	500							


Dimensions




- 9t grab, 30s cycle, 800t/h output
- 13m depth, 23m height, 24m radius
- Energy recovery, 20% savings
- Agile wheeled chassis

Scope Of Work

SMHW80 Lift capacities of material handler
(Boom10.5m, Stick7.5m, Unit:t)



SMHW80 Lift capacities of material handler
(Boom13m, Stick11m, Unit:t)




SMHC100



► Product Parameters


Technical Parameter					Configuration Parameter					
ITEM			UNIT	SMHC100	CONFIGURATION		UNIT	SMHC100		
Power System	Engine	Model	-	Deutz D09S3T9	Traveling Gear	Working Gauge	mm	6000		
		Rated Power	kw/rpm	260/2000		Wheel Base	mm	7420		
		Torque	Nm/rpm	1530/1200-1400		Track Width	mm	950		
		Emission	-	EU Stage III		Max.Travelling Speed	km/h	3		
		Oil Tank Capacity	L	600		Slewing Gear	Max. Rotating Speed	rpm	8	
	E-Motor	Model	-	-	Cabin	Cabin Lift Height	mm	3200		
		Rated Capacity	kW/rpm	-						
		Input Voltage	V/Hz	-						
Type Of Start	-	-								
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System	Basic Parameters	Boom Configuration	m	18	18	22
	Main Pump	Rated Flow	L/min	2×400			m	Boom 10.5	Boom 12.5	Boom 14.5
		Max. System Pressure	MPa	34			m	Stick 7.5	Stick 10	Stick 11
						Max. Operating Radius	m	18	22	24
						Max. Operating Height	m	24	27	29
				Max. Operating Depth	m	0	-3	-5		
Hydraulic Oil Tank		L	500	Max. Operating Radius (Grab Not Included)		t	9.0	7.5	5.0	

► Dimensions



► Scope Of Work

SMHC100 Lift capacities of material handler
(Boom10.5m, Stick7.5m, Unit:t)



- 9t grab, 30s cycle, 800t/h
- Energy-saving with regen & simulation
- 13m depth, 23m height, 24m reach
- Gantry chassis for rail yards


SMHC160



► Product Parameters


Configuration Parameter					Configuration Parameter				
ITEM		UNIT		SMHC160	CONFIGURATION		UNIT	SMHC160	
Power System	Engine	Model	-	Deutz D09S3T9A*2	Slewing Gear	Max. Rotating Speed	rpm	5	
		Rated power	kw/rpm	2*235/2000					
		Torque	Nm/rpm	2*1450/1200~1400	Cabin	Cabin Lift Height	m	Fixed Height increase2.3	
		Emission	-	Stage III /CN-4					
		Oil Tank Capacity	L	2200					
Chassis		Track Width	mm	6000	Basic Parameters	Boom Configuration	m	22	26
		Wheel Base	mm	7420			m	Boom 12	Boom 14.5
		Support Width (lengthways)	mm	8375			m	Stick 10	Stick 12
		Support Width (crosswise)	mm	7340			Max. Operating Radius (Excluding Spreader)	m	
		Turning Radius	mm	/					
		Max. Travelling Speed	km/h	3		Max. Operating Height (Excluding Spreader)	m	26	30
Hydraulic System		Type Of Control	-	Fully Electronically Controlled Positive Flow System		Max. Operating Depth (Excluding Spreader)	m	-3	-7
		Main Pump	Rated Flow	L/min		Max. Operating Radius (Grab Not Included)	t	21	13
		Maximum System Pressure	MPa	35					
		Hydraulic Oil Tank	L	1100					

► Dimensions




► Scope Of Work

SMHC160 Lift capacities of material handler
(Boom 12m, Stick 10m, Unit:t)



SMHC160 Lift capacities of material handler
(Boom 14.5m, Stick 12m, Unit:t)



- 13t grab, 30s cycle, 800t/h
- Energy recovery, 20% savings, 60-80L/h
- 24m radius with K22/K26 boom
- Gantry crawler chassis, 40% gradient


SMHR200



Product Parameters


Configuration Parameter					Configuration Parameter							
ITEM			UNIT	SMHR200	CONFIGURATION		UNIT	SMHR200				
Power System	Engine	Model	-	Deutz D13S3T9*2	Traveling Gear	Working Gauge	mm	10500				
		Rated power	kw/rpm	2*353/2000		Wheel Base	mm	10500				
		Torque	Nm/rpm	2*2350/1100~1500		Max.Travelling Speed	km/h	2				
		Emission	min	COM III/CN IV		Slewing Bearing	-	Sany				
	Fuel Tank	L	4000	Slewing Gear		Max.Rotating Speed	rpm	5				
	E-Moto	Model	-		XDYSP-4001-4 B35	Cabin	Cabin Lift Height	mm	2300			
		Rated Capacity	kW/rpm	2*355/1486	Basic Parameters	Boom Configuration	m	31	35			
Hydraulic System	Type Of Control		-	Electronically Controlled Positive Flow System			m	Boom 16	Boom 19.5			
							m	Stick 15	Stick 16			
	Main Pump	Model	-	Engine connection pump:kawasaki E-motor connection pump:kawasaki			Max. Operating Radius	m	30	32.5		
		Rated Flow	L/min	1920				m	32.5	36		
	Main Valve		-	Rexroth				Max. Operating Height	m	-10	-12	
	Reducer		-	Bonfiglioli				Max. Operating Depth	t	9.2	11.3	
	Boom Cylinder		-	Sany				Max. Operating Radius (Grab Not Included)				
	StickCylinder		-	Sany								
Max.System Pressure		MPa	34.3									
Hydraulic Oil Tank		L	1500									

Dimensions



Scope Of Work

SMHR200 Lift capacities of material handler
(Boom19.5m, Stick16m, Unit:t)



Efficiency:

- Load capacity can be more than 11.3 tons when 32.5m in horizon, 45 seconds when turn 90 degrees to operate in one working cycle, the average efficiency can reach 700 tons per hour.

Energy saving:

- Energy recovery system, saving energy efficiency 15% ,electrical control positive flow system, energy consumption reduce 5% ,comprehensive operation consumption about 60~80 Litre per hour.

Reliable:

- Suit for -45℃~+45℃ working condition,dynamic anti-tipping over protection and bracket protection against falling and loosening,automatic circular fire extinguishing system in engine room.

► Introduction to the New Generation Material Handler Cab

Aesthetics and Comfort



Orange-peel Grab

- Rocker switches have been replaced with push-button switches.
- One-touch start, cup holder, and emergency stop integrated into right armrest console.




Comfort Enhancements

- Standard electro-controlled air suspension heated seat
- Standard right-side roll-up curtain and front sunshade.


Exterior Upgrades

- Upgraded air vent design.
- Refreshed interior trim and more stylish armrest console.



Control System Updates

- Independent 10-inch touchscreen display
- Integrated controls for Bluetooth phone, music, radio, and AC
- Configurable camera display interface with four viewing modes
- Independent power supply for cab and upper platform with self-diagnosis
- Integrated controller for ignition switch and throttle knob
- EVI System



Overall Exterior Design



► Attachments

► Orange-peel Grab

Technical Parameter		
Capacity(m³)	0.8m³	1m³
Self-weight(kg)	1902	1952
Self weight without rotator(kg)	1675	1725
Width when expanded(mm)	2550	2933
Width when closed(mm)	1625	1822
Height with rotator(kg)	3093	3286
Height without rotator(kg)	2829	3022
Working pressure(Mpa)	30	30



► Timber Grab

Technical Parameter	
Looping area(m²)	Parameter
Self weight with rotator(kg)	2211
Looping area when expanded(mm)	3251
Looping area when closed(mm)	1638
Height/length(mm)	4028/810
Working pressure(Mpa)	28



► Clamshell Grab

Technical Parameter					
Capacity(m³)	2.0m³	2.5m³	3.5m³	4.0m³	5.0m³
Self-weight(kg)	2216	2404	2566	2752	2924
Self weight without rotator(kg)	1888	2090	2243	2318	2795
Length(mm)	1500	1602	1804	2000	2000
Width expanded(mm)	2470	2865	3112	2918	3228
Width closed(mm)	2218	2298	2668	2696	2595
Height with rotator(kg)	3270	3468	3597	3652	3629
Height without rotator(kg)	3006	3204	3333	3234	3458
Working pressure(Mpa)	30	30	30	30	30



► Steel Tube Grab

Technical Parameter	
Item	Parameter
Rated load(t)	8
Max. Rotate speed(r/min)	10
Rated working pressure(MPa)	25
Stretch Itinerary(mm)	single side 1420
Lateral distance(mm)	left 360/right 360
Steel tube length(m)	6-8.5
Spreader self weight(t)	2.5



► Pulp Grab

Technical Parameter	
Item	Parameter
Rated load(t)	6
Max. Rotate speed(r/min)	10
Movable hook open/close time(s)	< 1
Rated working pressure(mpa)	25
Spreader length(mm)	2600
Spreader width(mm)	1300
Spreader height(mm)	2150
Hook distance range(mm)	840 -2000
Spreader self weight(t)	1.5



► Generator System

Technical Parameter			
Item	WM5-110L WM5-130L WM5-160L		
Rate of power kW	25		
Electromagnet			
Item	ZKZL-19E-D		
Shape(mm)	520×350×750 (dimension)		
Output rate of work(kW)	25		
Input voltage(V)	AC380		
Output voltage(V)	DC220		
Protection level	IP45 (suitable for outdoor use)		
Magnetization & demagnetization time	≤3s		
Control cabinet			
Item	WM5-110L	WM5-130L	WM5-160L
Rated voltage(DC)	220V	220V	220V
Input rate of power (kW)	8.14	13.4	17.8
Diameter (m)	1.1	1.3	1.6
Self weight(kg)	around 1310	around 2100	around 3050
Cold current (a)	37	60.9	81
Protection level	IP67	IP67	IP67
Insulation level	H level	H level	H level
Cast iron mold(kg)	800	1100	2300
Cutting bits (kg)	800	1100	2300
No.1 Steel scalp(kg)	400	600	1100
No.2 Steel scrap(kg)	100	200	400
Type of connection	chain	chain	chain
Electromagnet outlet	YC2×10	YC2×16	YC2×16



Magnetic plate

► Construction Cases



Construction Cases (Inland Port)



Construction Cases (Rail Yard)



► Construction Cases (Cargo)



36T



48T



200T

SANY OVERSEAS SERVICE

GO WITH SANY NO MORE WAITING

900+



Overseas service centers

3500+



Professional technical service engineers

365×24



Support

Service Center

Tel: +86 4006098318

Mail: CRD@sany.com.cn

WhatsApp: +86 19908478631 (Only WhatsApp)



My SANY

On-demand professional equipment repair services available anytime, anywhere, ensuring rapid response and efficient solutions.



Download MySANY for a comprehensive, all-in-one experience!

DOWNLOAD ON THE
App Store

GET IT ON
Google Play

DOWNLOAD APK 6.0+
Android





SANY Industrial Park, Zhuhai, Guangdong, China

Service: +86-4008-87-8318 <https://www.sanyglobal.com>

Considering the continuous progress and update of SANY Marine technology, the technical parameters and configuration of products are modified and adjusted at any time, so this brochure is for reference only.

The appearance, configuration and technical parameters of the specific model are subject to the actual model sold. Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.

© Version 2026-01-14



Contact SANY Group



Follow SANY Group

SANY MARINE |   